

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
15 March 2001 (15.03.2001)


PCT

(10) International Publication Number
WO 01/18890 A1

- (51) International Patent Classification⁷: H01M 2/02, 8/04 (74) Agent: COHEN-ZEDEK, Nachman; Eitan, Pearl, Latzer & Cohen-Zedek, Gav Yam Center 2, Shenkar Street 7, 46725 Herzlia (IL).
- (21) International Application Number: PCT/IL00/00528
- (22) International Filing Date: 4 September 2000 (04.09.2000) (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 131842 9 September 1999 (09.09.1999) IL (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): UNIBAT LTD. [IL/IL]; Yozmot Haemek, P.O. Box 73, 10550 Migdal Ha'emek (IL).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): KLIATZKIN, Vladimir [IL/IL]; Alon Street 18, 29550 Kiryat Yam (IL). Published: — With international search report.

[Continued on next page]

(54) Title: CHARGEABLE ELECTROCHEMICAL CELL



(57) Abstract: An electrochemical cell for batteries comprising one or more pairs of electrodes (6). The first electrode is comprised of a flexible electrically insulating and ion conducting envelope (5) which contains a flexible conducting substrate (1). The flexible conductor (1) can be made of a conductive material in the form of fabric or grid, inserted into an active material in granular or powder form (2). The second electrode is also a flexible electrically insulating envelope (5) containing an electrical conductor (1) inserted into a layer of an electrochemically complementary active material. The cell also contains a means for applying pressure (4) to the assembly of electrodes, the membrane separator, and the counterelectrodes so as to maintain contact between the active material particles and the conductor. The assembly also contains a suitable electrolyte; electrode connections are provided from each of the envelopes.



— Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.